VAN BUREN SUBDIVISION (0415)

			VAIN		<u>, </u>
			Radio Display: Van Buren to Marche - 2424(*28) -		
		1	Marche to N. Little Rock -4242 -		
Mile	Rule	СР	SOUTH NORTH	Sta.	Siding
Post	6.3	#'s	▼ STATIONS ▲	#'s	Feet
498.5	TWC ABS		VAN BUREN BTY (12.5)	L 158	Yard
486.0			DYER (16.2)	L 146	7641
469.7			POPING B (13.2)	L 130	7602
456.5			(13.2) ALIX (13.1)	L 117	7602
443.0			SPADRA B (15.5)	L 105	7582
427.5			SCOTIA (9.8)	L 085	8219
417.7			RUSSELLVILLE T (0.1)	L 075	Yard
417.6			D. & R. CONN. B		
410.7			(0.5) WORTHEN (10.6)	L 068	7897
400.1			BLACKVILLE (18.8)	L 057	7755
381.3			MENIFEE (17.7)	L 038	7576
363.6			MAYFLOWER B (8.2)	L 021	10691
355.4 353.7	CTC	V355	MARCHE !	L 010	7796
344.3		V353 X343	VAN BUREN WYE (0.4)		
343.9		X342	LOCUST ST. (0.3)		
343.6			N. LITTLE ROCK B	X 344	Yard
		I			

(154.9)

SI-01 MAIN TRACK AUTHORITY

CTC Between MP 355.4 and MP 343.6. **ABS Between** MP 498.5 and MP 355.4.

TWC Between MP 495.8 and MP 355.4.

Yard Limits Between MP 498.5 and MP 495.8.

SI-02 MAXIMUM SPEED TABLE							
Maximum Spe	MPH						
Between Mileposts							
498.5 and	-						
	Below)	50					
498.5 and	496.5	20					
479.7 and	479.5	45					
474.5 and	471.6	40					
467.3 and	464.3	45					
Between Mi	leposts						
446.4 and	395.0						
(Except as	Below)	60					
	434.5						
	426.8						
	423.6						
	415.0						
	412.8						
	411.1						
402.3 and	401.9	50					
Between Mileposts							
395.0 and 343.6							
	Below)						
	391.4						
	385.9						
	371.0						
	359.3						
	357.5						
346.0 and	344.2	25					
SI-03 OTHERS	SPEED RESTRICTIONS						

SI-03 OTHER SPEED RESTRICTIONS

Maximum Speed

1.	Thru	Sidings	&	Turnou	ts				
	_					-	_	_	

Thru turnout at south switch Spadra.... 15

MPH

2. Dual Control Switch Turnouts (No Exceptions.)

SI-04 MAIN TRACK DESIGNATIONS - None.

SI-05 MILEPOST EQUATIONS - None.

SI-06 DTC BLOCK LIMITS - None.

SI-07 ITEM 13 TRAIN DEFECT DETECTORS

(#) 488.3	(#) 433.4	(#) 384.2
(#) 463.9	(#) 419.0	(#) 368.6
(#) 447.3	(#) 403.0	

SI-08 RULES ITEMS

Van Buren: Rule 8.3 does not apply to spring switches located at the north end of Trk. 1 MP 498.3 and at the south end of Trk. 1 MP 496.5 to a train equipped with end-of-train device and no employee available to handle switch. Switches may be left lined and locked for Trk. 1.

Before D&R trains or engines enter Union Pacific main track at Russellville, permission must be obtained from train dispather.

SI-09 FRA EXCEPTED TRACKS

Camp Robinson - tracks. 752, 755, 757 thru 769.

VAN BUREN SUBDIVISION (0415)

SI-10 BUSINESS TRACKS		
Track Name	ИP	STA. #'S
Alma4	89.4	L149
Mulberry4	79.7	L140
Ozark4	64.8	L125
Co-op Spur N4	62.9	L123
Carbon S4	59.2	L120
Clarksville4	35.6	L093
Knoxville4	33.6	L091
AP&L S4	24.5	L083
Cargill S4	23.4	L082
Atkins N4	05.8	L063
Morrilton3	92.5	L050
Conway3	73.1	L030
AP &L No. 2 N	62.3	L019
Maumelle N3	55.3	L013
Levy S3	45.7	L003

SI-11 INDUSTRIAL LEADS

Conway Industrial Lead: MP 371.6 - At all crossings, a crew member must be on the ground at the crossing to warn traffic until crossing is occupied. Maximum speed 5 MPH on entire leaq.

SI-12 TONNAGE RESTRICTIONS/TPOB

Maximum gross weight: 143 Tons.

SI-13 TRAIN MAKE-UP RESTRICTIONS - None.

SI-14 MISC. INSTRUCTIONS

Morrilton Business Track (old siding) MP 392.5. A crew member must be on the ground at the crossing to warn traffic until crossing is occupied, at Stevens Street MP 391.9.

Conway Business Track (old siding) MP 373.1 ---. At all crossings, a crew member must be on the ground at the crossing to warn traffic until crossing is occupied.

Road Crossing: Trains must stop short of road crossings at Spadra, AR., as long as possible when making train meets to keep crossings clear. Any trains that will not clear the crossing at Spadra will not stop their train to eat at Lazy Earl's at or about MP 444.5.

Turning Locomotives: When turning locomotives on wye track at Van Buren, turn only one unit at a time. Six axle units must not be turned on this wye unless authorized by a Manager.